



«MAGNITO-KONTAKT» Ltd

51B, place H4, Novaya St., 390027 Ryazan, Russia, phone +7 915 622-20-57
E-mail: 453788@bk.ru; 451694@bk.ru /m-kontakt.ru/ /m-kontakt.com/

EXPLOSION-PROOF COUPLING DEVICES US-2, US-2M

Ex

1Ex db IIC T6...T5 Gb / 0Ex ia IIC T6...T5 Ga

INGRESS PROTECTION RATING
IP66/IP68



Ex US-2 WITHOUT MOUNTING PLATFORM
Ex US-2M WITH MOUNTING PAD



Description

Ex connection devices US-2 and US-2M are designed for connecting (branching) signal cables.

Material of Ex-connection device US-2 is stainless steel.

Coupling devices is equipped with exchangeable metal cable glands quantity 2 pcs.

Coupling devices can be fitted with threaded adapters.

The cable glands and adapters are made of stainless steel, corrosion-resistant steel, brass or corrosion-resistant brass.

Ex US-2 and Ex US-2M are equipped with plastic terminal blocks with a cable diameter from 2.5 mm² to 10 mm². The number of terminal pairs is 8.

Operating temperature **from - 60°C to + 95°C.**

Weight: **from 0.8 to 3.5 kg.**

Dimensions

Dimensions in mm

